

FRAME AND SEAT SELECTIONS

9SL 9000SL K0004

FRAME WIDTH AND DEPTH

- WD66 16" x 16"
- WD68 16" x 18"
- WD86 18" x 16"
- WD88 18" x 18"
- WD06 20" x 16"
- WD08 20" x 18"

SEAT-TO-FLOOR HEIGHT

Based on 24" wheels and 8" casters. See seat-to-floor matrix.

- Adult 19 1/2" STF No Charge
- Hemi 17 1/2" STF No Charge

ARM AND BACK OPTIONS

ARM TYPE

Fixed height arms are 10", adjustable height arms 10"-14".

- 19 Full Length Adj Height Conv
Flip-back conventional removable arm style, must ANGLE back.
- 29 Desk Length Adj Height Conv
Flip-back conventional removable arm style, must ANGLE back.
- 78 Full Length Fixed Height Space - Saver
Flip back non-removable arm style.
Not available with adjustable angle back type.
- 79 Full Length Adj Height Space - Saver
Flip back non-removable arm style.
Not available with adjustable angle back type.
- 88 Desk Length Fixed Height Space - Saver
Flip back non-removable arm style.
Not available with adjustable angle back type.
- 89 Desk Length Adj Height Space - Saver
Flip back non-removable arm style.
Not available with adjustable angle back type.

BACK TYPE

- ANGLE Adjustable Angle Back with 10° Bend
Not available with space - saver arms. Standard with tippers. Adjustable height 15" - 19", factory set at 16".

BACK HEIGHT

Not available with adjustable angle back type. BH1517 is factory set at 16" high. BH1719 is factory set at 18" high.

- BH1517 Adjustable Back Height 15" - 17"
- BH1719 Adjustable Back Height 17" - 19"

COLOR OPTIONS

FRAME FINISH

- 08P Deep Purple
- 24P Wet Black
- 34P Satin (Flat) Black
- 71P Silver Vein

UPHOLSTERY COLORS

- U240 Black Nylon
- U67 Black Vinyl

WHEELS

WHEEL OPTIONS

- U1763BK 20" Composite Urethane Tires
Not available with urethane rear wheels.
- U1764BK 22" Composite Urethane Tires
- 2244BK 24" Composite Pneumatic Tires
- 4244BK 24" Composite Pneumatic Flat Free Inserts ..
- U2244BK 24" Composite Urethane Treaded Tires
- U2222C 24" Composite Corded Urethane Tires

WHEEL LOCKS

- 9690B Pull To Lock Wheel Locks (Std on Hemi) ... No Charge
- 9691B Push To Lock Wheel Locks (Std on Adult) . No Charge

HANDRIM OPTIONS

- AHDRM Aluminum Handrims
Not available with standard U2222C rear wheels.
- COM Composite Handrims
Only available with 24" rear wheels.

CASTERS

CASTER OPTIONS

- AT902 6" Composite Urethane 3 Spoke
- AT903 8" x 1 1/4" Composite Urethane
- 1299 8" x 1" Solid Rubber Casters
- 1292 8" x 1 1/4" Pneu Casters
- 1492 8" x 1 1/4" Pneu with Flat Free Inserts

POSITIONING STRAP OPTIONS

SEAT POSITIONING STRAPS

- 1515 Push Button Style Seat Positioning Strap
- 1321BK Hoop and Loop Seat Positioning Strap

FRONT RIGGING OPTIONS

FRONT RIGGINGS

- AHL4A Hemi Smartleg Artic Legrests Alum Ftplt
- AHL4C Hemi Smartleg Artic Lgrsts Comp Ftplt
- T93HA Hemi Sw Ftrsts Alum. Ftplt with Heel Loops ...
- T93HC Hemi Sw Ftrsts Comp Ftplt with Heel Loops ...
- T94HA Hemi Sw Elev Legrests Alum Ftplt
- T94HC Hemi Sw Elev Legrests Comp Ftplt
- T93HE Hemi Footrest without Loop Comp Ftplt
- T94HE Hemi Legrest Comp w/Blk Non Rem Calf Pad.

FOOTPLATE OPTIONS

- 1350 Extra Large Aluminum Footplates

FOOTREST/LEGREST ACCESSORIES

- 1820 Non - Removable Device
Not available with AHL4A or AHL4C Articulating L
- 1346 Heel Loops
Heel Loops are standard on Swingaway Footrests
- L8689 Omit Heel Loops

ACCESSORIES

BACK ACCESSORIES

- L8601 Omit Back Upholstery.....
- 1160 Carrying Pocket.....
- STC Stencil Back Upholstery.....

SEAT ACCESSORIES

- L8651 Omit Seat Upholstery.....
- 9120 Solid Seat Insert.....

ARM ACCESSORIES

- NRAS Non-Removable Arm with Screws.....

MISCELLANEOUS ACCESSORIES

- 9357L Amputee Attachment.....
- 1577QR Quick Release Axles.....
- 2218 IV Rod, Telescopic.....
- 2226 Front Anti Tippers.....

STOCK OPTIONS

- 1497 Oxygen Holder Pkg Assembly.....
- 1496 IV / Oxygen Holder Package Assembly.....
- 1360 Adj. Rear Anti - Tippers (8" Casters).....
Standard with adjustable angle back.
- 1360A Adj. Rear Anti - Tippers (6" Casters).....
- A1576 Wheel Lock Extensions.....
- 1100 Tool Kit.....

Seat-to-Floor Matrix 6" Casters			
Seat-to-Floor Height	Front Caster Mounting Position	Rear Wheel Size	Rear Wheel Mounting Position
15 1/2"	Top	20"	Top
16 1/2"	Middle	22"	Top
17 1/2"	Bottom	24"	Top
17 1/2"	Bottom	20"	Bottom

Seat-to-Floor Matrix 8" Casters			
Seat-to-Floor Height	Front Caster Mounting Position	Rear Wheel Size	Rear Wheel Mounting Position
17 1/2"	Top	20"	Bottom
17 1/2"	Top	24"	Top
18 1/2"	Middle	22"	Bottom
19 1/2"	Bottom	24"	Bottom

Weight Limitation 250 Pounds

Invacare recommends all wheelchairs be fitted to the consumer under the guidance of a healthcare professional, knowledgeable of the particular limitations of the product.

Comments

