

# Specifications & Listings



## Three GoLift Weight Capacities

**GO**Lift 400

Single Lift  
GO-LIFT-400

Lift Up to  
400 lbs / 181 kg

### Safe Working Load (SWL)

400 lbs / 181 kg

### Dimensions

- Length: 7 ¾" / 197 mm
- Width: 7 ¾" / 197 mm
- Height: 4 ¼" / 108 mm
- Strap Length: 84" / 2134 mm

### Unit Weight

400 lb / 181 kg version: 8 lbs / 4 kg

### Lift Case

Flame retardant ABS

### Safety

Emergency Stop  
Emergency Lowering Device  
Upper Limit Detection  
Lower Limit Detection  
Slack Tape Sensor  
Free Fall Brake (over speed governor)  
Low Battery and Dead Battery Alarms  
Soft Start and Stop  
Overload Protection  
Emergency Manual Lowering

### Approvals

Certified to:  
Can/CSA-C22.2 No 60601-1:08,  
UL 60601-1:08  
Tested to: ISO 10535-06, CE

### Hand Control

Capacitive Touch  
Protection Class: IPX0

### Service Life

10 years or 22,500 cycles

### Maximum Sound Level

<55 dB

### Maximum Lifting Speed

No load: 2 inches/second  
150 lbs / 68 kg: 1.3 inches/second  
400 lbs / 181 kg: 1 inch/second

### Batteries

High Capacity, Nickel Metal Hydride (Ni-Mh)  
Standard: 2 x 14.4V (2Ah)  
Optional: 2 x 14.4V (3.3Ah) or (5Ah)

### Battery Charger:

100-240 VAC 40 Watt

### Number of Lifts per Charge (Duty: 10/90)

25% of strap at midrange<sup>1</sup>:

- 375 with 185 lbs / 84 kg
- 170 with 400 lbs / 181 kg
- 102 with 700 lbs / 318 kg

Charging time: 2 - 4 hours

<sup>1</sup> Calculated using 5Ah Packs

