

Removable Tub Bench INSTALLATION INSTRUCTIONS

THIS PRODUCT SHOULD BE INSTALLED BY QUALIFIED PERSONNEL

1. Determine desired tub seat location.

The seat must be located on the bathtub so that the swing-down legs are perpendicular to the Tub Bench, and that the leveling feet are positioned on a clean, FLAT surface.



Swing down the legs 90 degrees until the "Locking Pin" snaps through the hole in the leg bracket, into its stopping position. The legs will be locked in their "down" position.

2. Determine seat height from the floor and location relative to the tub and bathroom finished floor.

ADA guidelines advise a finished seat height of 17" to 19" above the bathroom finished floor.

Place the tub clamp over the front of the tub ledge. Level and lock the adjustable feet. Tighten the Tub Clamp to secure the seat onto the tub ledge.

Do not "over-tighten" the Tub Clamp, which may distort the Tub Clamp Bracket.

3. Check Bench for:

- 1) Correct finished height.
- 2) Tub Clamp properly secured on tub ledge.
- 3) "Swing Down Legs" locked in down position @ **90 degrees**, perpendicular to the tub floor.
- 4) The rubber leveling feet must be positioned on a FLAT surface to the tub floor. (Not resting on the radius corner of the tub.)

Storing the Bench:

- Loosen clamps and remove the bench.
- Push the spring clip in **FIRST** then fold legs.

If the FEET of the Installed Bench do not sit on a FLAT surface, contact Accessible Designs Inc as soon as possible

