

drawing no. D11-0920-34

date originated

9/20/2011

Ε

D. HAGAN

® Bodypoint[®]

technical bulletin

						technical bulletin
	PUSH-BUTTON BUCKLE & COVERS Light-weight, low-profile, superior strenght & durability. Requires 5 lb-f (22 N) of force to release.		PLASTIC SIDE-RELEASE Lightweight, secure snap action.	REHAB LATCH Light-weight, strong, low-profile, easy to operate with limited hand function. Requires < 1 bif. (4.5 N) of force to release when unloaded. Requires 12 lb-f (53 N) of force to release at 300 lb-f of tension.	SWIVEL BUCKLE Light-weight, strong, and low-profile. Swivel action allows closing up to 45° off centerline. 90° of rotation while buckled.	X-SMALL METAL PUSH-BUTTON Strong, secure, child-sized buckle. Requires 4.5 lb-f (20 N) of force to release.
-532 -538			1-1/4" 1-1/4" FS002 1" SIDE RELEASE		1-1/8"	FS029-BP BUCKLE WITH ADJUSTABLE TONGUE
FITS 1" WEBBING			F5012 1" DUAL SIDE RELEASE (USED ON DUAL-PULL BELTS ONLY)		F5035 1" SWIVEL BUCKLE Requires 10# (45 N) of force to release.	FS029-BP BUCKLE WITH FIXED TONGUE (USED ON REAR-PULL BELTS ONLY)
-M36 -M40 -M46 FITS 1-1/2" WEBBING	1-3/4" R 22mm HOLE	FS018D-1 REDUCED ACCESS COVER 6mm HOLE	FS003 1-1/2" SIDE RELEASE FS013 1-1/2" DUAL SIDE RELEASE	1-3/-4"	1-7/8"	
WEDDING.	FS018 1-1/2" PUSH-BUTTON BUCKLE	FS018C-1 SECURITY COVER	(USED ON DUAL-PULL BELT'S ONLY)	FS016 1-1/2" REHAB LATCH BUCKLE	FS036 1-1/2" SWIVEL BUCKLE Requires 12# (53 N) of force to release.	
-L62 -L82 -L92	2-3/8"	FS019D-1 REDUCED ACCESS COVER	2-3/8" 3-1/8" 55004 2" SIDE RELEASE	2-1/8"		
FITS 2" WEBBING	22mm HOLE FS019 2" PUSH-BUTTON BUCKLE	FS019C-1 SECURITY COVER	FS014 2" DUAL SIDE RELEASE (USED ON DUAL-PULL BELTS ONLY)	FS017 2" REHAB LATCH BUCKLE		
note					description	T DUCK ES TESTINGS (* SDES)
DIMENSIONS ARE FOR REFERENCE ONLY.					HIP BEL	T BUCKLES TECHNICAL SPECS