

Contact Name: _____
Street Address: _____
City, State, Zip: _____
Phone: _____
Email: _____



Quotes@RehabMart.com
1-800-827-8283
3651 Mars Hill Rd, Bldg 2400
Watkinsville, GA 30677-6042
USA

- size **Small**
- size **Medium**
- Frame colour: **black**
- Upholstery colour: **dark grey/green-green**
 dark grey/pink-pink
 light grey/green-green
 light grey/pink-pink



ACCORDING TO THE ISO
7176/19 and
ANSI RESNA WC/19

**M
E
A
S
U
R
E
S**



	A (cm)	B (cm)	C (cm)	D (cm)	E (cm)	F (cm)	G (degrees)	J (degrees)	H (cm)	I (cm)	L (cm)	M (cm)	N (cm)	O (cm)	P (cm)	Q (cm)	R (cm)	S (cm)	max. load	frame weight	seat weight	total weight
Small	20-30	52-62	37	52	20-30	14-30	0°-35°	35°	100-110	57	67-96	35	88	33	82	50	81	90-120	35 kg	9,5 kg	8,5 kg	18 kg
Medium	25-36	60-75	46	55	30-40	20-38	5°-30°	40°	112-127	62	80-107	37	112	39	94	52	94	115-140	45 kg	11 kg	12,7 kg	23,7 kg

Hypen-separated numbers indicate the minimum and maximum range of adjustment

SEAT UNIT, the only one with a tilt-in-space system incorporated in the seat

- HEADREST incorporated in the backrest: your child's head is always supported during the tilt adjustments of the seat and of the backrest, also without accessories.
- Rigid BACKREST, reclinable and adjustable in height. The hinge coincides with the child's pelvis physiological fulcrum.
- Tilt-in-space SEAT, adjustable in width and depth. Reversible (size Small, base 869).
- Fireproof, recyclable FABRIC. Colours durable and highly resistant to sweat, light, dry cleaning and washing. Maximum resistance to rubbing. Oeko-Tex Certificate - for textile products intended for all fabrics that are in direct contact with the skin, a guarantee of quality and safety for health.
- Tip-up FOOTREST, flexion-extension adjustable, with legrest adjustable in height and tilt; the hinge coincides with the child's knee physiological fulcrum.

869 OUTDOOR four wheels base - CRASH TESTED ISO 7176/19 and ANSI RESNA WC/19

- Foldable aluminium FRAME. Push-handle adjustable in tilt: it adapts to the mother's height and reduces the encumbrance of the pushchair.
- Puncture proof WHEELS, light and easy to push on every surface: front 17 cm with directional locks; rear 25 cm (size Small) or 30 cm (size Medium), with shock absorbers and independent drum brakes.

856 - 851 indoor high-low bases, 850 indoor compact floor base

- Foldable FRAME in steel. Adjustable in height. It is easy and safe to use, thanks to a gas spring mechanism, hand lever (base 851) and foot pedal (base 856)
- 10 cm swivelling WHEELS with brakes (for base 856)
- 7.5 cm swivelling WHEELS with brakes (for base 851)



Attention!
Read carefully the user and
maintenance manual

BUG MODULAR SEATING SYSTEM

Tested by BERLIN CERT GmbH and listed in the GERMAN HMV
(Technical Aids Listing)
Certified by CERAH France
FDA registered (USA)
CE Marked

ADDITIONAL COMPONENTS

<p><input type="checkbox"/> 863 Multiadjustable Headrest with parietal supports</p> 	<p><input type="checkbox"/> 852 Headrest with parietal supports</p> 	<p>942 Ergonomic headrest for Bug Small</p> <p><input type="checkbox"/> S <input type="checkbox"/> M</p> 	<p><input type="checkbox"/> 835 Shaped headrest</p> 	<p><input type="checkbox"/> 838 Adjustable lateral supports</p> 	<p><input type="checkbox"/> 894 45° pelvic belt</p> 
<p><input type="checkbox"/> 868 Adjustable wrappable and flexible trunk supports</p> 	<p><input type="checkbox"/> 834 Padded abduction block</p> 	<p><input type="checkbox"/> 834R Adjustable padded abduction block</p> 	<p><input type="checkbox"/> 853 Vest harness</p> 	<p><input type="checkbox"/> 903 Five point vest harness</p> 	<p><input type="checkbox"/> 906 Five point harness</p> 
<p><input type="checkbox"/> 920 4 point belt</p> 	<p><input type="checkbox"/> 827 Foot straps</p> 	<p><input type="checkbox"/> 839 Adjustable front handle</p> 	<p><input type="checkbox"/> 824 Adjustable transparent tray</p> 	<p><input type="checkbox"/> 824B Wide tray only for 850-851-856 indoor bases.</p> 	
<p><input type="checkbox"/> 935 Oxygen bottle holder</p> <p>Maximum dimensions of the oxygen bottle: height 600 mm (valve included) - diameter 140 mm.</p> 	<p><input type="checkbox"/> 911 Vent tray</p> 		<p><input type="checkbox"/> 819 Canopy black/green</p> <p><input type="checkbox"/> 819 Canopy black/pink</p> 	<p><input type="checkbox"/> 825 Rain cover (to fix at the canopy 819) for 869 base</p> 	<p><input type="checkbox"/> 818 Thermal cover</p> 
<p><input type="checkbox"/> 892 Padded covering for footrest</p> 	<p><input type="checkbox"/> 858 Net basket for 869 base</p> 	<p><input type="checkbox"/> 922 Bottle holder for 869 base</p> 	<p><input type="checkbox"/> 891 Set of 4 tie down hooks for the forward-facing transport of the pushchair in a motor vehicle (private/cars, buses...). Only for 869 base</p> <p>CRASH TESTED</p> <p>CONFORME ISO 7176/19 e ANSI RESNA WC/19</p> 		
<p><input type="checkbox"/> 817 Leg straps</p> 	<p><input type="checkbox"/> 850 Indoor compact floor base</p> 	<p><input type="checkbox"/> 856 Indoor high-low feeding base</p> 			