

Colorado Spring Bathing System



HCPCS:



FIGURE A



FIGURE B



FIGURE C



FIGURE D



FIGURE E



FIGURE F



FIGURE G

- Thermostatic mixing valve - Provides an anti-scald protection that dispenses 15 gallons per minute for fast tub fill
- Built-in disinfection system - The most time-efficient solution for disinfection of the baths external surfaces and minimizes the risk of cross-infection
- The built-in disinfection system cabinet is conveniently located on the front of the tub for easy access
- The lockable cabinet provides a secure place for cleaning supplies and disinfectants
- Shower wand - Hair and upper body washing can be used at the same time the tub is filling
- Water temperature display - Monitors tub-fill and shower wand temperatures
- 3/4" supply lines - Constructed of stainless steel mesh clad
- Lap and shoulder harness - Used for resident safety
- Secondary door lock - Prevents accidental door opening when in use
- The CleanDrive Air Spa System - Variable speeds and pulse modes designed to enhance the bathing experience for the resident and caregiver
- Redesigned height adjustable legs for a more streamlined look (Insert E)

PRODUCTS

Description

DB-COLORADO-1000	Side Entry w Thermo Valve
DB-COLORADO-1100	Side Entry w Disinfect, Thermo Valve
DB-COLORADO-1200	Side Entry w Disinfect, ThermoValve & A

SPECIFICATIONS

Description

Dimensions	33.5" (W) x 61.5" (L) x 42.5"
Door Configuration	Right Hinge Only
Drain Size	1.5"
Drain Time	1 Minute, 58 Seconds
Electrical Supply	115V AC, 60Hz, 15 amp
Fill Time	3 Minutes, 10 Seconds
Height	35"
Seat Dimensions	21.5" (W) x 21" (H)
Threshold Height	11"
Transfer Device Access	44" (W) x 7" (H)
Water Capacity (Occupied)	48 Gallons
Water Supply Inlet	3/4" Diameter
Weight Capacity	600 lbs