Freedom Accessible Shower Pan 60" x 32"

FREEDOM INSPIRE SERIES

MODEL APX6032BFP LR

Note: Shower pan LH drain shown

Exterior Dimensions: $60W \times 32D \times 6H$

Interior Dimensions: 57 W x 26 % D clear floor space



COLOR & TRIM OPTIONS

Standard Color	Code
White	WT

FEATURES

- I-piece Barrier Free Shower Pan
- Pre-levelled shower base, no recess necessary (concrete or slab floor, drain area does require a 10" x 10")
- Textured slip-resistant floor
- Left or right drain location, ideal for bathtub replacement
- Drain included, square plate, chrome finish, no caulk
- Works with all wall materials and finishes
- Adaptable for shower doors
- Consistent nailing flange
- Underside of pan is smooth and pre-leveled for easy installation

OPTIONS

(All accessories shipped loose for field installation)

- Standard and Deluxe Accessory Kits available
- Collapsible water retainer with end caps
- Pressure balance valve
- Hand held shower with slide bar
- Weighted shower curtain and rod
- Folding shower seat
- Grab bars

CODE COMPLIANCE

- IPC International Plumbing Code
- UPC Uniform Plumbing Code
- ANSI Z124.2 Standards for Plastic Showers
- CSA Canadian Standards Association

Due to the nature of the materials, dimensions may vary +- 1/2".

Lifetime Limited Warranty

*See terms and conditions for details.








Freedom Accessible Shower Pan 60" x 32"


FREEDOM INSPIRE SERIES

MODEL APX6032BFP LR

FRONT VIEW




TOP VIEW






COMES WITH NO CAULK DRAIN and Square Strainer Plate

Cutaway Drain Detail





FEATURES Dimensional Tolerance ± ½". Dimensions needed for site preparation should be measured from the unit. Accessibility Professionals Inc. assumes no responsibility for prep work.

Model #	Material	Wall Finish	Pieces	Pkg. Wt.
APX6032BFP LR	Applied Acrylic	N/A	1	89 Crated

DIMENSIONS

Specifications	inches	
Exterior Dimensions	60 × 32 × 6	
Interior Dimensions	57 × 26 % clear floor space	
Shower Door Opening	57 1 ⁄2 W	

FRAME-IN DIMENSIONS

Α	В	С	D
60 1/4	8 %16	15	32

