



JAY® FUSION® with Cryo™ Technology

Introducing CryoFluid, the new revolutionary fluid option available for the JAY Fusion cushion that excels at reducing the risk of pressure injuries. Patent-pending CryoFluid is now being offered alongside industry favorite, JAY Flow™ Fluid, to provide your patients with more options for skin protection.

CryoFluid actively cools a patient's seated skin surface for up to 8 hours* while evenly distributing pressure, reducing shear, and lowering the risk of moisture.



Heat leaves skin surface,
cooling the skin



A long lasting effect



SUPERIOR CLINICAL SEATING

JAY® FUSION

CUSHION WITH CRYO TECHNOLOGY

INNOVATIVE DESIGN TECHNOLOGY

- X-STATIC® stretch outer cover reduces tension and resists bacterial growth
- JAY CryoFluid insert is designed for skin protection, actively lowers the skin temperature and evenly distributes pressure
- Inner cover with AquaGuard® moisture resistant zipper and anti-wicking thread for moisture protection

SIMPLE TO FIT

- Pelvic Loading Area (PLA) well and insert sized around anthropometric data, specific for each cushion width
- Pre-contoured foam base with high-resiliency posterior pelvic wall design encourages orthopedic alignment
- The CryoFLuid PLA insert is divided into 5 chambers, the two chambers under the ischial tuberosities (ITs) include CryoFluid and the other three chambers include industry favorite, JAY Flow™ Fluid
- Also available in a Positioning Option and Reduced Profile Option

SIMPLE TO ORDER

- Smart part numbers and a wide range of available modifications
- JAY-Your-Way customizations available



Specifications:

HCPCS Codes
E2622, E2623,
E2624, E2625

Width
16" to 22"

Depth
16" to 22"

Height
3 3/8" to 4"

Weight Capacity
300 lbs for 16" to 21"
500 lbs for 22"

Base
Pre-contoured, closed cell
high resiliency foam

Insert
JAY CryoFluid

Inner Cover
Moisture-resistant with
AquaGuard zipper, anti-
wicking seam thread

Outer Cover
X-STATIC silver
thread stretch

JAY TECHNOLOGY IN THE FUSION WITH CRYOFLUID



LAYERED
SUPPORT



CONTOURING



POSITIONING



PRESSURE
DISTRIBUTION



FOUR WAY
STRETCH



ACTIVE
COOLING