

There is Power Mobility. And then there's

POWERFUL MOBILITY



MiniRider
Lite



There is Power Mobility. And then there's

POWERFUL MOBILITY

MiniRider Lite

The MiniRider Lite is a transportable scooter with the stability of a 4-wheel scooter and the turning radius of a 3-wheeler, providing the customer greater maneuverability. With a 280 lb load capacity and 4 wheels, the MiniRider Lite can transport higher weighted individuals with stability not usually found in portable scooters.



MAX SPEED
4.0
MPH



LOAD CAPACITY
280
LBS



BATTERY
12 Ah
SLA



RANGE
28
MILES

Length	42.5"
Width	19"
Height	36"
Front section	35 lbs
Rear section	26 lbs
Battery pack	20 lbs
Seat	16 lbs
Weight with batteries	92 lbs
without battery	72 lbs
Battery	12 AH (option 18AH)

Charger	2A Off-Board
Tire Size	8" x 2"
Front Tire	200X50 PU TIRE
Rear tire	200X50 PU TIRE
Ground clearance	3"
Seat height	23"
Seat height - cushion to deck	20"
Seat	Fish on seat
Seat width	17"
Seat depth	16"
Top Speed	4 mph

Battery range 12V 12AH SLA Battery	Up to 10 miles
Battery range 12V 18AH SLA Battery	Up to 18 miles
Turning radius	52"
Wheelbase	31"
Climbing angle	8 degrees
Motor size	270 Watts
Max. user weight	280 lbs
Controller	Curtis 45A
Colors	Red, Green, Silver, Blue

(*) SPECIFICATION PERFORMANCE IS DETERMINED IN THE LABORATORY SETTING BASED ON IDEAL CONDITIONS (MINIMAL FRICTION, NO WIND AND CONTROLLED TEMPERATURE AND PRESSURE WITH AN AVERAGE STANDARD WEIGHT). ACTUAL PERFORMANCE WILL BE DIFFERENT THAN RESULTS OBTAINED DURING LABORATORY TESTING.