

# MTD 4000

## Specifications

Power Supply	AC 110V~120V, 50/60Hz AC 220V~240V, 50/60Hz
Power Consumption	100 W (Max.)
Fuse	2.0 A/ 250 V× 2 Slow Blow 1.0 A/ 250 V× 2 Slow Blow
Maximum Output Force	90 Kg / 198 lb
Traction Speed	Fast — ~5-6 seconds to reach maximum force Normal — ~12-15 seconds to reach maximum force Slow — ~22-25 seconds to reach maximum force
Hold / Rest Period	1 ~ 99 seconds
Treatment Time	1 ~ 99 minutes
Treatment Mode	Continuous / Intermittent
Security System	Error Codes E-1 ~ E-A
Display	Yellow / Green Digital LED Display
Patient Safety Switch	2 Pin connector, push button normally closed
Electromagnetic Compatibility	IEC 60601-1-2
Medical Device Classification	Class IIa as per MDD 93/42/EEC, Annex IX
CE Marking	CE 0434
Operation Temperature/Humidity	0~40°C / 90%RH under
Storage Temperature/Humidity	-20~60°C / 90%RH under
Dimension	L 14.2" x W 12.2" x T 9" (L 36 cm x W 31 cm x T 22.9 cm)
Net Weight	32 pounds (14.5 kg)