



Portable
Room-to-Room
Unique Design



Our Rooter S overhead lift is a portable lift that offers the possibility to transfer a patient from one room to another in one single motion without making modifications to doorway headers.

A Comfortable Experience

The Rooter S offers optimum comfort when used with our sling portfolio. The room-to-room function reduces the number of lifts required and minimizes strain on both the patient and the caregiver. It offers a soft-start, soft-stop and constant lifting speed regardless of the patient weight and direction, making lifting a comfortable experience. The lift has a weight capacity of 220kg/484lb and can be used with either a 2, 3 or 4-point suspension.

Unique Design

The Rooter S is suitable for rooms with sliding doors or fire doors as no modification to the doorway is required, thus making installation

much easier. For facilities, its unique design eliminates the need for turntables and rail switches. The Rooter S also features a lightweight quick release hanger bar in two different widths to accommodate most lifting situations. Charging can be done through the hand control for optimal efficiency.

Lift Intelligence

The Rooter S features an advanced technology platform that allows tracking of lift usage and visualization of collected data. This integrated lift intelligence allows data to be retrieved using our Data and Service Application on a tablet or computer. Detailed information can be viewed directly in the application or exported to other media for additional analysis.

Accessories



Hanger bar

Quick release for optimal convenience. Order separately. Part no.: 55751 (45cm/17.7") 55764 (55cm/21.7")



Powered spreader bar

For use with clip slings in hospital or other care environments. Part no.: Small 92441, Medium 92442, Large 92443



Handset

Two speed with up/down mode. Input for charging and USB interface. IPX5 water protection rating. Part no.: 71457




Upholstered Cover

Protects user from hanger bar impact. Hanger bar sold separately. Part no. 50866



Lift charger

Charger with holder. Easily attaches to wall. Part no. 50899-US



Gates and Turntables

Offering additional lift transfer options on rails. Part no. 55721 (Gate), 91884 (Turntable)



4-point suspension

Enables 4-point lifting. Placed on leg hook. Part no.: 55619



Distance Strap

Reinforced nylon thread and metal hooks. Extend lift strap up to 100cm/39.3". Part no. 20124-xx (specify length)



Secondary Control

Secondary control panel on back of lift for emergency stop function. Integrated feature.




Cart

Simplifies transport of lift between rooms. Convenient sling storage. Part no.: 50346



Scale

Medical grade scale. Max. capacity 320kg/705.5lb. ISO and EN compliant. Part no.: 50348, 50345 (Canada)



Insights

Lift intelligence that facilitates cloud based storage of collected data. Integrated feature.

Technical Specifications

Description	Roomer S		
Part Number (Lift)	55300H-[Country Code]	Part Number (Hanger Bar)	55751 (45cm/17.7") 55764 (55cm/21.7")
Dimensions (W x H x L)	40cm x 16cm x 30cm 15.7" x 6.2" x 11.8"		
Safe Working Load	220kg/484lb		
Product Weight (Lift)	9.9kg / 21.7lb		
Product Weight (Hanger Bar)	1.3kg/2.8lb (55751) or 1.5kg/3.3lb (55764)		
Battery	2.3Ah, 2x12V		
Battery Charger	Input: 100-240V, AC 50-60 Hz Output: 27.8V, 0.8A DC		
IP Class	Lift: IPX4 Hand Control: IPX5		
Lifting Distance and Speed	Distance: 208cm/81.9" Speed: 1.8m/min - 3m/min — 70"/min - 118"/min		
Approvals	ROHS-2 approved, Tested and approved according to ISO 10535:2006 ETL Listed		
Emergency Lowering	Electronic and Mechanical		

This product is manufactured in accordance with all relevant ISO standards.



Learn more about this product



Country Codes: AU-Australia, GB-Great Britan, EU-Europe, JP-Japan, NA-North America