

## Saratoga Spring Bathing System

HCPCS:



FIGURE A



FIGURE B



FIGURE C



FIGURE D



FIGURE E

- Thermostatic mixing valve - Provides an anti-scald protection that dispenses 15 gallons per minute for fast tub fill
- Built-in disinfection system - The most time-efficient solution for disinfection of the baths external surfaces and minimizes the risk of cross-infection
- The built-in disinfection system cabinet is conveniently located on the back end of the tub for easy access
- The lockable cabinet provides a secure place for cleaning supplies and disinfectants
- Handheld shower wand - Hair and upper body washing can be used at the same time the tub is filling
- Water temperature display - Monitors tub-fill and shower wand temperatures
- 3/4" supply lines - Constructed of stainless steel mesh clad
- Three plumbing configurations - to choose from side, front, or island configuration
- The island configuration allows 360° unobstructed access for the caregiver and with no visible hook-ups or cords, the Saratoga Springs Bathing System will give the bathing area the look of a luxury spa
- The CleanDrive Air Spa System - Variable speeds and pulse modes designed to enhance the bathing experience for the resident and caregiver

### PRODUCTS

	Description
DB-SARATOGA-1100	Reclining Tub w Thermo Valve, Disinfect
DB-SARATOGA-1200	Reclining Tub w Thermo Valve, Disinfect

### SPECIFICATIONS

	Description
Dimensions	34" (W) x 73" (L) x 51" (H)
Door Configuration	Upward Swing, Left Hinge Only
Drain Size	1.5"
Drain Time	2 Minutes, 10 Seconds
Electrical Supply	115V AC, 60Hz, 15 amp
Fill Time	2 Minutes, 10 Seconds
Height	78"
Length Reclined	88"
Seat Dimensions	24" (W) x 21" (H)
Transfer Device Access	7" (W) x 31" (H)
Water Capacity (Occupied)	38 Gallons occupied   24 Gallons foot well
Water Supply Inlet	3/4" Diameter
Weight Capacity	450 lbs for Resident   730 lbs for Resident and Water