

PLEASE SAVE THESE INSTRUCTIONS FOR FUTURE USE


Info: The most current version of these instructions can be found online at www.grahamfield.com.

- ⚠ WARNING: Important! Read and understand these instructions before assembling or using the Full-Body Sling. If you do not understand any part of these warnings, cautions or instructions, contact a healthcare professional for direction in the use of this product. If the Full-Body Sling is not properly applied, personal injury and damage to the Full-Body Sling could result.

- ⚠ WARNING: DO NOT exceed the Full-Body Sling's maximum weight capacity.

APPLICATION

- 1. Check the patient's weight and the sling's maximum weight capacity. Ensure that the patient's weight does not exceed the sling's maximum weight capacity.
- 2. Review the following procedures carefully before attempting lift; call Graham-Field Technical Support at 678-291-3207 with any questions.
- 3. See the Sling Loop Options table at right to determine the appropriate position.



Sling Loop Options				
Long loop	reclined position			
Center loops	semi-reclined position			
Short loop	most upright position			







Figure 2




Figure 3



Figure 4

- 4. See Figure 1 for correct positioning of sling on spreader bar.
- 5. Position the sling under and behind the patient's back with the color adjustment strap on outside. Drape **A** and **B** over the shoulders as shown in Figure 2.
- 6. Carefully, with help from another caregiver, if needed, pull the sling portion **C** and **D** forward to the bend of the knee as shown in Figure 2.
- 7. Hook sling loops **A** and **B** to spreader bar **a** and **b** as shown in Figure 3.
- 8. Hook sling loops **C** and **D** to spreader bar **c** and **d** as shown in Figure 3.
- 9. Do not lock caster brakes, in order to allow the lift to properly balance weight.
- 10. Proceed with lift and transfer as shown in Figure 4.

MAINTENANCE

To clean sling, use a mild soap and water solution and a clean cloth. Rinse with clear water, then allow to air dry.

▲ NOTICE: DO NOT use bleach, solvents, abrasive cleaners, or scouring pads on any part of the sling.

WARRANTY

GF Health Products, Inc. offers a six-month limited warranty against manufacturer's defects on the Full-Body Sling. If a product is deemed to be under warranty, GF Health Products, Inc. shall provide, at its option, (1) replacement of any defective part or product or (2) a credit of the original selling price made to GF Health Products, Inc.'s initial customer. The warranty does not include any labor charges incurred in replacement part(s) installation or any associated freight or shipping charges to GF Health Products, Inc.


The warranties contained herein contain all the representations and warranties with respect to the subject matter of this document, and supersede all prior negotiations, agreements and understandings with respect thereto. The recipient of this document hereby acknowledges and represents that it has not relied on any representation, assertion, guarantee, warranty, collateral contract or other assurance, except those set out in this document.


FEATURES


Mesh Full-Body Commode Sling					
Quick-draining/drying mesh fabric offers full head and neck support. For use with 4-point spreader option. Designed to meet the requirements of HCPCS Code E0621.					
FMC114	Medium	1 ea			
FMC115	Large	1 ea			
FMC116	X Large	1 ea			
FMC141	Heavy Duty XX Large	1 ea			

Mesh Full-Body Sling				
Quick-draining/drying mesh fabric offers full head and neck support. For use with 4-point spreader option. Designed to meet the requirements of HCPCS Code E0621.				
FM110	Medium	1 ea		
FM111	Large	1 ea		
FM140	Heavy Duty, XX Large	1 ea		
	_			

Solid Full-Body Sling				
Fully-padded fabric offers a soft, yet support surface. Offers full head and neck support. For use with 4-point spreader option. Designed to meet the requirements of HCPCS Code E0621.				
F112	Medium	1 ea		
F113	Large	1 ea		
F117	X Large	1 ea		







ITEM	Size	Body Width	Body Length	Commode Opening to Top of Back (FMC114, FMC115, FMC116, FMC141 only)	Maximum Weight Capacity, EVENLY DISTRIBUTED
FM110, F112, FMC114	Medium	42 3/4"	50 ³ /4"	34 3/4"	450 lb
FM111,F113, FMC115	Large	44 3/4"	54 1/4"	38"	450 lb
FMC116, F117	X Large	44 3/4"	60 1/4"	43"	450 lb
FM140, FMC141	Heavy Duty, XX Large	42"	51"	41 1/2"	600 lb

