



SportsPlay™

We Put the Value in Play!

SportsPlay Equipment, Inc.
500 Delmar Blvd, Ste G, St Louis, MO 63124
(314) 389-4140 (800) 727-8180 Fax (314) 389-9034
www.sportsplayinc.com

SWING SEAT SPECIFICATIONS

582-955 Cut Proof Belt Seat:

Swing seats shall be 6" x 24" molded rubber with steel plate inserts. Hardware shall be zinc coated. S-Hooks shall be 3/8" O.D., 3" long zinc coated.

582-961 Toddler Safety Belt Seat:

Seat shall be fabricated from Nylock Koroseal nylon reinforced rubber belting with rivets. "D" rings shall be 3/8" zinc plated steel. Strap shall be 1/0 chain with plastic cover and swivel snaps.

582-964 Infant Seat

Seat shall be fabricated from Nylock Koroseal nylon reinforced rubber belting with rivets. "D" rings shall be 3/8" zinc plated steel.

382-411 ADA Jenn Swing Seat

Seat is a patented rotational molded plastic seat designed with a partially-reclined, body-embracing design, complete with an adjustable safety harness. Accommodates children up to 125 lbs. and is 14"W x 11" deep, with a seat back length of 24". Knee to foot length is 14" and overall length is 45".